

## DSL information

STORE MAIN( ) or REMOTE( )

Address: \_\_\_\_\_  
: \_\_\_\_\_  
City & State: \_\_\_\_\_  
Voice Phone: \_\_\_\_\_

DSL PROVIDER NAME: \_\_\_\_\_ Ex. Verizon, Bellsouth ..

DSL PHONE #: \_\_\_\_\_

TECH SUPPORT PHONE #: \_\_\_\_\_

DSL MODEM MODEL#: \_\_\_\_\_

STATIC IP: \_\_\_\_\_ Ex. 168.123.167.XXX

SUB NET MASK: \_\_\_\_\_ 255.255.255.XXX

GATEWAY: \_\_\_\_\_ 168.123.167.XXX

DNS PRIMARY: \_\_\_\_\_ 67.156.168.202

SECONDARY: \_\_\_\_\_ 67.156.102.201

IF DSL uses PPPoE add the following information

PPPoE User Name: \_\_\_\_\_ Ex. [john@bellsouth.net](mailto:john@bellsouth.net)

Password: \_\_\_\_\_ xyz1234

**When you request the DSL line the modem provided by the ISP needs to be in bridge mode.**

**The Static IP or Gateway addresses can not be in the following range:**

**10.0.0.0 – 10.255.255.255**

**172.16.0.0 – 172.31.255.255**

**192.168.0.0 – 192.168.255.255**

**Speed: 1.5 Mbps/256 Kbps minimum**